

CAFE & RESORT UMBRELLA



Features at a glance

- Simple and easy to open and close
- Heavy-duty double pulley system
- Commercial grade pulley rope
- Glass-filled nylon high-performance hubs and brackets
- Marine grade anodised aluminium frame and pole
- Stainless steel fastenings and components
- Commercial strength pole with a large diameter and thick aluminium wall.



All Shadowspec SU2 Umbrellas have eight full strength 20mm x 33mm / 3/4" x 1 1/8" struts arms.

Canopy

- Premium 100% solution dyed canopy
- Maintenance: All fabrics can be washed and are replaceable
- Shade Rating: UPF 50+

Colour Options*



Egg Shell White



Black Widow



Cobalt Blue



Rich Red



Boulder Grey



Lemon Yellow

*other non stock colours available on request.

Custom Branding

We specialise in custom branding umbrellas with your logo/brand and message.



BEST-IN-CLASS WARRANTY

Relax easy knowing your outdoor umbrella purchase is protected by the industries best warranty and customer support.



Fabric
Warranty



Frame
Warranty

SU2

CAFE & RESORT UMBRELLA

Mounting Options



Steel Flat Plate Base
Single plate (approx 30kgs) recommended for 2.0m / 6'7" square. & 2.7m / 8'10" octagon sizes.

Double plate recommended for 3.0m / 9'8" sq & 4.0m / 13'1" oct sizes.



Concrete Base
Is suitable for 2.0m / 6'7" square & 2.7m / 8'10" Octagon sizes only.



Surface Plate
Bolt down mounting option. Suitable for all SU2 sizes.

Size & Configuration


2.0m / 6'7"




2.7m / 8'10"



3.0m / 9'10"



4.0m / 13'1"



Umbrella Dimensions



Diagram Legend

	2.0m / 6'7"	2.7m / 8'10"	3.0m / 9'10"	4.0m / 13'1"
A Overall Height*	2600mm / 8'6"	2645mm / 8'8"	2935mm / 9'8"	2850mm / 9'4"
B Clearance of Closed Strut Arms*	1150mm / 3'10"	1250mm / 4'1"	780mm / 2'7"	815mm / 2'8"
C Canopy Width*	2000mm / 6'7" sq.	2700mm / 8'10" dia.	3000mm / 9'10" sq.	4000mm / 13'1" dia.
D Head Clearance*	2200mm / 7'3"	2200mm / 7'3"	2295mm / 7'6"	2260mm / 7'5"
E Pole outside diameter	38mm / 1½"	38mm / 1½"	48mm / 2"	48mm / 2"

Note: All measurements are rounded and are subject to change.

Adding portable base wheels also will add a further 45-80mm/2-3"